

## Ecotile ESD Conductive Tape Guide

Quantity of linear metres of tape required per m<sup>2</sup> of Ecotile ESD Flooring -  
Round up to the higher 50m (i.e. 117m = 150 of tape)

m <sup>2</sup>	Square Root of m <sup>2</sup>	Linear Meters of Tape Required
25	5.00	58
50	7.07	117
75	8.66	175
100	10.00	233
125	11.18	292
150	12.25	350
175	13.23	408
200	14.14	467
225	15.00	525
250	15.81	583
275	16.58	642
300	17.32	700
325	18.03	758
350	18.71	817
375	19.36	875
400	20.00	933
425	20.62	992
450	21.21	1,050
475	21.79	1,108
500	22.36	1,167
525	22.91	1,225
550	23.45	1,283
575	23.98	1,342
600	24.49	1,400
625	25.00	1,458
650	25.50	1,517
675	25.98	1,575
700	26.46	1,633
725	26.93	1,692
750	27.39	1,750
775	27.84	1,808
800	28.28	1,867
825	28.72	1,925
850	29.15	1,983
875	29.58	2,042
900	30.00	2,100
925	30.41	2,158
950	30.82	2,217
975	31.22	2,275
1000	31.62	2,333

Last Review 03/12/2024

Next Review 03/12/2026